PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:
A61M 15/00
(11) International Publication Number: WO 99/12596
(43) International Publication Date: 18 March 1999 (18.03.99)

(21) International Application Number: PCT/EP98/05592

(22) International Filing Date: 3 September 1998 (03.09.98)

(30) Priority Data:
MU 7702049-9 5 September 1997 (05.09.97) BR

(71) Applicant (for all designated States except US): CHIESI FAR-MACEUTICI S.P.A. [IT/IT]; Via Palermo, 26/A, I-43100 Parma (IT).

(72) Inventors; and

(75) Inventors/Applicants (for US only): CHIESI, Paolo [IT/IT]; Via Palermo, 26/A, I-43100 Parma (IT). DEL CORNO, Marco [IT/IT]; Via Romilli, 29, I-20139 Milano (IT). PANZA, Isabella [IT/IT]; Via Palermo, 26/A, I-43100 Parma (IT). VENTURA, Paolo [IT/IT]; Via Palermo, 26/A, I-43100 Parma (IT).

(74) Agent: MINOJA, Fabrizio; Bianchetti Bracco Minoja S.r.l.; Via Rossini, 8, I-20122 Milano (IT).


(81) Designated States: AL (Utility model), AM (Utility model), AT, AT (Utility model), AU (Petty patent), AZ, BA, BB, BG (Utility model), BR, BY, CA, CH, CN (Utility model), CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, GH, GM, HR, HU (Utility model), ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX (Utility model), NO, NZ, PL (Utility model), PT, RO, RU (Utility model), SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR (Utility model), TT, UA (Utility model), UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: NOZZLE FOR USE IN MOUTH-INHALING FOR AEROSOL MEDICAMENTS



(57) Abstract

An aerosol nozzle, comprising a socket provided with a seat to house a hollow stem of an aerosol dispensing pressurized can, said nozzle being shaped as a T, consisting of an upper bar and of a vertical stem, characterized in that the hole of said nozzle through which the aerosol dose is discharged is inclined with respect to the plane normal to the axis of said vertical stem.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	_	ES	Spain	LS	Lesotho	SI	Slovenia	
AM	Amenia	ì	FI	Finland	LT	Lithuania	SK	Slovakia	
AT	Austria	,	FR	France	LU	Luxembourg	SN	Senegal	
AU	Australia		GA	Gabon	LV	Latvia	SZ	Swaziland	
AZ	Azerbaijan		GB	United Kingdom	MC	Мопасо	TD	Chad	
BA	Bosnia and Herzegovina		GE	Georgia	MD	Republic of Moldova	TG	Togo	
BB	Barbados		GH	Ghana	MG	Madagascar	TJ	Tajikistan	
BE	Belgium		GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan	
BF	Burkina Faso		GR	Greece		Republic of Macedonia	TR	Turkey	
BG BG	Bulgaria		IIU	Hungary	ML	Mali	TT	Trinidad and Tobago	
	Benin		IE	Ireland	MN	Mongolia	UA	Ukraine	
BJ BR	Brazil		IL	Israel	MR	Mauritania	UG	Uganda	
BY	Belarus		IS	Iceland	MW	Malawi	US	United States of America	
CA	Canada	-	IT	Italy —	MX.	_Mexico _	UZ	Uzbekistan	
CF	Central African Republic		JР	Japan	NE	Niger	VN	Viet Nam	
CG	Congo		KE	Kenya	NL	Netherlands	YU	Yugoslavia	
CH	Switzerland		KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe	
CI	Côte d'Ivoire		KP	Democratic People's	NZ	New Zealand			
CM	Cameroon		•••	Republic of Korea	PL	Poland			
CN	China		KR	Republic of Korea	PT	Portugal			
CU	Cuba		ΚZ	Kazakstan	RO	Romania			
cz	Czech Republic		LC	Saint Lucia	RU	Russian Federation			
DE	Germany		LI	Liechtenstein	SD	Sudan			
DK	Denmark		LK	Sri Lanka	SE	Sweden			
EE	Estonia		LR	Liberia	SG	Singapore			
	- Constitu					- -			

WO 99/12596 PCT/EP98/05592

NOZZLE FOR USE IN MOUTH-INHALING FOR AEROSOL MEDICAMENTS

The present invention relates to an aerosol nozzle, comprising a socket provided with a seat to house a hollow stem of an aerosol dispensing pressurized can.

Inhalation is the preferred system for delivering medicament particles into the lungs.

5

10

30

For this purpose pressurized cans containing the medicament and a propellant are used, the cans being provided with a metering valve which when manually operated dispenses metered doses of propellant-medicament mixture which atomizes through a nozzle as a finely powdered spray into the mouth of a patient.

It is generally known that only about 10% of the aerosol dose discharged by a pressurized can is capable to reach the lungs.

A similar percentage is expired or is deposited outside the oral cavity, whereas because of the impact of the high speed particles about 80% is deposited within the oropharyngeal cavity, swallowed systemically adsorbed and hence practically lost.

If the pressurized can is not used properly the quantity of medicament which reaches the site of action at the pulmonary level is further reduced and the therapeutic response is compromised.

25 Excessive aerosol depositing in the oropharyngeal cavity can also lead to undesirable effects either at systemic level as a consequence of the drug absorption, or at the local level, as in the case of corticosteroids, which can result in oral candidiasis.

The reasons for poor pulmonary penetration are known.

WO 99/12596

20

Even if a dispensing can for aerosol medicaments is used correctly, the availability of an inhaled medicament to the lungs depends largely on the size of the aerosol droplets.

The only particles that can penetrate into the lungs is any significant degree are those whose diameter is 1-5 thousandths of a millimetre (microns). An inhalation aerosol spray only contains a small amount of such particles as most of the medicament is bound to considerably larger droplets formed by a non-volatile propellant.

Thus, it is obvious that by reducing the droplet size of a spray it is also possible to reduce the particle size and hence to improve the pulmonary penetration of a medicament and the size of droplets is reduced as the volatilization of a propellant proceeds.

In an attempt to overcome the problems connected with the use of aerosol medicament, auxiliary delivery systems have been developed over the last decade for application to the nozzles of pressurized dispensing cans.

In the european patent EP-B-0475257 a mouth-inhaling device for use with pressurized cans for dispensing metered doses of medicament is described.

Said device is designed to favour the inhaling of a greater number of active particles and to avoid spraying the aerosol directly onto the mucosa of the oropharynx in order to safeguard the user against side effects deriving from direct spray into the mouth.

In this respect, the device has an expansion chamber shaped to create, by virtue of the speed at which the aerosolized material is expelled by the dispenser, a

vortex flow in which the particles remain in suspension for sufficient time to enable them to discharge their kinetic energy and allow substantial evaporation of the propellant, with a consequent reduction in the size and in the velocity of the particles, leading to a more efficient intrapulmonary delivery, while large size particles are centrifuged onto the walls of the chamber, to deposit on them.

The device comprises a body with a seat for housing a can provided with a stem for operating the can dispensing valve, a chamber for the collection and expansion of the aerosol dispensed by a discharge nozzle on the can, and a mouthpiece communicating with said chamber and projecting outwards from said body. The body has a substantially flat shape and the chamber is delimited by a curved wall, into a first peripheral portion of which there opens the inner end of the mouthpiece, and in a second peripheral portions of which, opposite the first, there is an aperture from which two walls extend outwards from the chamber to converge towards the can discharge nozzle and define a duct, the central plane of which is inclined to the central plane of said mouthpiece.

The aerosol dispensed by the can, when operated, penetrates into the expansion chamber and expands to circulate with a vortex flow which causes the solvent to evaporate and the flow movement to continue for a relatively long time, hence enabling only very small particles of the medicament to be drawn into the bronchial tree.

The structure and characteristics of the inhales device are illustrated in Figure 1 to 4 in which:

PCT/EP98/05592 WO 99/12596

Figure 1 is a perspective view of the inhaler device; Figure 2 shows one of the two shells forming the device, viewed in the direction indicated by the lines 2-2of Figure 1; and

Figure 3 and 4 are sections through the inhaler device on the lines 3-3 and 4-4 of Figure 1.

It can be seen from Figure 2 that in a peripheral portion of the curved wall 10, opposite that from which the mouthpiece 4 projects, there is an aperture from which two walls 11 and 21, respectively (Figure 4), extend outwards from the chamber to converge (Figure 2) towards the exit hole of the nozzle and define a duct for the medicament flow.

It is now unexpectedly found that the circulation with a vortex flow into the expansion chamber can be favoured and improved by a particular realization of the nozzle wherein the hole through which the aerosol dose is discharged is inclined (Figure 8).

15

20

In accordance with the present invention there is provided an aerosol nozzle having the shape of a T consisting of an upper horizontal bar and a vertical stem, said stem comprising a socket with a seat for housing a hollow stem of a pressurized can, characterized in that the hole of the vertical stem of the nozzle through which 25 a dose of medicament discharged from a metering valve finds its way into the expansion chamber is inclined with respect to the hollow stem of the pressurized can.

Specific embodiments of the invention will now be described, with reference to the accompanying drawings, in which:

Figure 5 is a front view of the T shaped nozzle;

WO 99/12596

15

25

30

Figure 6 is a side view of the T shaped nozzle; Figure 7 is a top view of the T shaped nozzle;

Figure 8 is a section view of the nozzle along lines A-A of the Figures 5 and 7, showing the socket provided with a seat to house a hollow stem of a pressurized can and the inclined hole through which a dose of medicament discharged from the valve enters into the expansion chamber.

The nozzle (1) is shaped as a T, consisting of an upper bar composed by two fins (2, 3) to be housed and retained in two seats provided in the two shells forming the device and of a vertical stem (4) shorter than the horizontal upper bar.

The vertical stem (4) comprises a socket (5) provided with a seat to house a hollow stem of a pressurized can.

In the thickness of the stem (4) is bored a hole (6) that connects the socket (5) with the expansion chamber of the device through the orifice (7).

The hole (6) is inclined with respect to the plane B normal to the axis of the vertical stem (4).

When a pressurized can has been housed in the device, with the valve stem inserted into the seat of the socket (5) of the nozzle (1) and the base of the can is pressed with one finger, the dispensing valve within the can opens and a measured quantity of aerosol is discharged.

The discharged aerosol passes through the inclined hole (6) and emerges through the orifice (7) as a cone whose axis is inclined with respect to the plane B.

The axis of the hole and of the emerging aerosol cone forms with the plane B an angle in the range of 20 to 30° and preferably of 27°.

WO 99/12596 PCT/EP98/05592

- 6 -

The internal diameter of the hole (6) is in the range of 0.40 to 0.55 mm and is preferably of 0.42 to 0.52 mm.

The inclination of the hole is designed in a manner that the aerosol cone issuing from the nozzle orifice passes through the duct defined by the two walls 11 and 21 of Figures 3 and 4 extending outwards from the expansion chamber and converging towards the exit hole of the nozzle.

The inclination of the hole is designed in a manner that the axis of said aerosol cone corresponds with the central plane of the ducts.

It is so avoided any possible deviation of the aerosol jet resulting from the impact of a part of the aerosol cone against the diverging walls 11 and 21.

15

The aerosol cone penetrates into the expansion chamber and generates within the chamber a vortex motion which results in deposition of the largest particles on the walls whereas the other particles lose their layer of propellant and hence reduce in diameter with an increase of the respirable fraction.

CLAIMS

20


- 1. An aerosol nozzle, comprising a socket provided with a seat to house a hollow stem of an aerosol dispensing pressurized can, said nozzle being shaped as a T, consisting of an upper bar and of a vertical stem, characterized in that the hole of said nozzle through which the aerosol dose is discharged is inclined with respect to the plane normal to the axis of said vertical stem.
 - 2. A nozzle as claimed in claim 1, characterized in that the axis of the hole and the plane normal to the axis of the stem form an angle in the range of 20 to 30° and preferably of 27°.
- 15 3. A nozzle as claimed in claims 1 and 2 wherein the internal diameter of the hole is in the range of 0.40 to 0.55 mm and preferably of 0.42 to 0.52 mm.
 - 4. An aerosol nozzle substantially as herein described, with reference to, and as illustrated in, Fig.5 to 8 of the accompanying drawings.
- 5. A nozzle as claimed in claims 1 to 4 to be housed in a device for mouth inhaling medicaments dispensed as aerosols by pressurized cans, comprising a body with a seat for housing a can provided with a stem for operating the can dispensing valve, a chamber for the collection and expansion of the aerosol dispensed by a discharged nozzle of the can, and an inhalation mouthpieced communicating with said chamber and projecting outwards from said body, wherein the body is of substantially flat shape, che chamber si delimited by a curved wall, into a first peripheral


WO 99/12596 PCT/EP98/05592

- 8 -


5


portion of which there opens the inner end of said mouthpiece, and in a second peripheral portion of which, opposite the first, there is an aperture from which two walls extend outwards from the chamber to converge towards the can discharge nozzle and define a duct the centre plane of which is inclined to the centre plane of said mouthpiece, characterized in that the aerosol discharged by the can circulates within the chamber with a vortex flow.











INTERNATIONAL SEARCH REPORT

intern: al Application No PCT/EP 98/05592

A. CLASSIF IPC 6	A61M15/00		
	•		
	International Patent Classification (IPC) or to both national classification	on and IPC	:
B. FIELDS S	SEARCHED cumentation searched (classification system followed by classification	(elodmye	
IPC 6	A61M	·	
			<u> </u>
Documentati	ion searched other than minimum documentation to the extent that suc	ch documents are included in the fields sea	ırched
Electronic da	ata base consulted during the international search (name of data base	and, where practical, search terms used)	
			,
	THE PARTY OF PER STANT		
	ENTS CONSIDERED TO BE RELEVANT Citation of document, with indication, where appropriate, of the relevance.	vant passages	Relevant to claim No.
Category *	Citation of document, with indication, where appropriate, of the refer		
х	EP 0 475 257 A (CHIESI FARMA SPA)		1,5
	18 March 1992 cited in the application		
Y	see column 4, line 34 - column 5, figures	line 23;	2,3
Y	GB 1 128 655 A (VANTOREX LTD.)		2
· 	2 October 1968 see page 2, line 85 - line 99; fig	gure 2	
Υ	US 5 622 162 A (RITSON CARL ET A		3
'	22 April 1997 see column 14, paragraph 4; figure		
			•
А	US 3 517 667 A (BABBIN SAUL A ET A 30 June 1970	AL)	2
	see claims 1,2; figures		
ļ		/	
1		,	. <u></u>
X Furt	I ther documents are listed in the continuation of box C.	X Patent family members are listed	in annex.
° Special ca	ategories of cited documents:	"T" later document published after the inte	mational filing date
"A" docum-	ent defining the general state of the art which is not dered to be of particular relevance	or priority date and not in conflict with cited to understand the principle or the invention	ne application but eory underlying the
	document but published on or after the international	"X" document of particular relevance; the c	be considered to
"L" docume which	ent which may throw doubts on priority claim(s) or is cited to establish the publication date of another	involve an inventive step when the do "Y" document of particular rejevance; the o	cument is taken alone laimed invention
"O" docum	on or other special reason (as specified) nent referring to an oral disclosure, use, exhibition or	cannot be considered to involve an in- document is combined with one or mo ments, such combination being obvious	ore other such docu-
"P" docum	means nent published prior to the international filing date but than the priority date claimed	in the art. "&" document member of the same patent	
	e actual completion of the international search	Date of mailing of the international se-	arch report
5	5 January 1999	14/01/1999	
Name and	mailing address of the ISA	Authorized officer	
	European Patent Office, P.B. 5818 Patentiaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo ni,	Villocomo 1 M	
	Fax: (+31-70) 340-3016	Villeneuve, J-M	

1

INTERNATIONAL SEARCH REPORT

Intern: al Application No
PCT/EP 98/05592

	tion) DOCUMENTS CONSIDERED TO BE RELEVANT	Relevant to claim No.		
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.		
A	GB 2 276 101 A (CSB MOULDS LTD) 21 September 1994			
,		·		
	·			

1

INTERNATIONAL SEARCH REPORT

Interna vi Application No PCT/EP 98/05592

Patent document cited in search report		Publication date			Publication date
EP 0475257	A	18-03-1992	IT AT AU CA DE DE DK ES FI HU IE JP NO NZ PT US	1244441 B 107521 T 642037 B 8373491 A 2051172 A 69102602 D 69102602 T 475257 T 2061139 T 914212 A 210440 B 65894 B 6023048 A 300798 B 239626 A 98956 A 5165391 A	15-07-1994 15-07-1994 07-10-1993 19-03-1992 14-03-1992 28-07-1994 06-10-1994 01-08-1994 01-12-1994 14-03-1992 28-04-1995 29-11-1995 01-02-1994 28-07-1997 26-01-1994 30-11-1993 24-11-1992
GB 1128655	Α		NONE		
US 5622162	A	22-04-1997	US US US AU WO CA EP JP US	5392768 A 5404871 A 5755218 A 6130394 A 9416757 A 2082168 C 0529053 A 9164205 A 2613347 B 5394866 A 5469750 A 5450336 A 9215353 A 5522378 A 5542410 A 55497764 A 5520166 A 5608647 A 5655516 A 5743252 A 5813397 A 5826570 A	28-02-1995 11-04-1995 26-05-1998 15-08-1994 04-08-1994 26-03-1996 03-03-1993 24-06-1997 28-05-1997 07-03-1995 12-09-1995 17-09-1995 17-09-1992 04-06-1996 06-08-1996 12-03-1996 28-05-1996 04-03-1997 12-08-1997 28-04-1998 29-09-1998 27-10-1998
US 3517667	Α	30-06-1970	NONE		
GB 2276101	Α	21-09-1994	NONE	Ξ	